

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 28/08/2019 Revision date: : Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Product name : ENEOS Sustina 0W-20

Product code : V161500400
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Intended for general public

Main use category : industrial use, professional use, consumer use

Use of the substance/mixture : Lubricant

Function or use category : Lubricants and additives

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

JX NIPPON OIL & ENERGY EUROPE LIMITED 4th Floor, 4 Moorgate London, EC2R 6DA UNITED KINGDOM

#### 1.4. Emergency telephone number

Emergency number : 0044 20 7186 0400

(Monday to Friday: 8:00 - 17:00)

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.

### 2.3. Other hazards

Other hazards not contributing to the classification

: This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as T/R45: May cause cancer" (Note L).". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
Lubricating oils	(CAS-No.) 74869-22-0 (EC-No.) 278-012-2 (REACH-no) 01-2119495601-36	>= 50	Not classified

10/01/2020 EN (English) 1/7

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils	(CAS-No.) 74869-22-0 (EC-No.) 278-012-2 (REACH-no) 01-2119495601-36	>= 50	Asp. Tox. 1, H304

Full text of H-statements: see section 16

OFOTIO		
	N 4: First aid	magelirae
SECTION	1 T. I II SI AIU	III Gagair Gg

#### **Description of first aid measures**

First-aid measures general

First-aid measures after inhalation

First-aid measures after skin contact

First-aid measures after eye contact

First-aid measures after ingestion

: Seek medical attention if ill effect develops.

Take victim to fresh air, in a quiet place, in an half laying position and if necessary take medical

Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. High-pressure injection under skin may cause serious damage. Seek medical attention if ill effect or irritation develops.

Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain, blinking, tears or redness persist.

: Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Do not induce vomiting.

#### Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation

At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

Symptoms/effects after skin contact

Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Symptoms/effects after eye contact Symptoms/effects after ingestion

: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs. Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger

quantities may cause nausea and diarrhoea.

Symptoms/effects upon intravenous

administration

## Indication of any immediate medical attention and special treatment needed

Treat symptomatically

#### **SECTION 5: Firefighting measures**

#### **Extinguishing media**

Suitable extinguishing media : Carbon dioxide (CO2), dry chemical powder, foam, Water fog.

Unsuitable extinguishing media : Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### Special hazards arising from the substance or mixture

Fire hazard : Combustion generates: CO, CO2, POx, NOx, SOx, H2S. Metal oxides. Explosion hazard : Not expected to be a fire/explosion hazard under normal conditions of use.

Reactivity : Stable under normal conditions of use.

#### **Advice for firefighters**

Precautionary measures fire : Do not enter fire area without proper protective equipment, including respiratory protection.

Firefighting instructions : Use water spray or fog for cooling exposed containers.

Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, Other information clearly marked container for disposal in accordance with local regulations.

### **SECTION 6: Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

General measures : Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters

#### 6.1.1. For non-emergency personnel

Protective equipment : When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of

splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.

: Consider evacuation. **Emergency procedures** 

10/01/2020 EN (English) 2/7

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

#### 6.1.2. For emergency responders

Protective equipment

: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

**Emergency procedures** 

: No specific measures are necessary.

#### 6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

#### 6.3. Methods and material for containment and cleaning up

For containment

: Large quantities: Contain large spillage with sand or earth.

Methods for cleaning up

: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Take up large spills with pump or vacuum and finish with dry chemical absorbent.

Other information

: Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. On water, recover/skim from surface and pour out in disposal container.

## 6.4. Reference to other sections

For further information refer to section 13.

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed

: Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

Precautions for safe handling

: Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Where contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes.

Hygiene measures

: Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact with eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep container tightly closed and in well ventilated place.

Storage conditions : Store in original container.

Incompatible products : Reacts vigorously with strong oxidizers and acids.

Maximum storage period : 5 year Storage temperature :  $\leq$  40 °C

Information on mixed storage : Keep away from : oxidizing materials. strong acids.

Storage area : Store at ambient temperature.

Special rules on packaging : Keep container tightly closed and dry.

### 7.3. Specific end use(s)

No additional information available

#### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

Lubricating oils (74869-22-0)		
Belgium	Limit value (mg/m³)	5 mg/m³ mist
Belgium	Short time value (mg/m³)	10 mg/m³ mist
Bulgaria	OEL TWA (mg/m³)	5 mg/m³
Greece	OEL TWA (mg/m³)	5 mg/m³ mist
Italy	OEL TWA (mg/m³)	5 mg/m <sup>3</sup>
Spain	VLA-ED (mg/m³)	5 mg/m³ mist
Spain	VLA-EC (mg/m³)	10 mg/m³ mist
Netherlands	Grenswaarde TGG 15MIN (mg/m³)	5 mg/m³ mist
Czech Republic	Expoziční limity (PEL) (mg/m³)	5 mg/m <sup>3</sup> Aerosol
Czech Republic	Expoziční limity (NPK-P) (mg/m³)	10 mg/m³ Aerosol
Denmark	Grænseværdie (kortvarig) (mg/m³)	1 mg/m³
Denmark	Grænseværdie (kortvarig) (ppm)	mist

10/01/2020 EN (English) 3/7

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Lubricating oils (74869-22-0)		
Hungary	AK-érték	5 mg/m³ mist
Ireland	OEL (15 min ref) (mg/m3)	0.2 mg/m <sup>3</sup>
Lithuania	IPRV (mg/m³)	1 mg/m³ mist
Lithuania	TPRV (mg/m³)	3 mg/m³ mist
Norway	Grenseverdier (Korttidsverdi) (mg/m3)	1 mg/m³ mist
Poland	NDS (mg/m³)	10 mg/m³ Aerosol
Poland	NDSP (mg/m³)	5 mg/m³ Aerosol
Romania	OEL TWA (mg/m³)	5 mg/m³
Romania	OEL STEL (mg/m³)	10 mg/m³
Slovakia	NPHV (priemerná) (mg/m³)	1 mg/m³ mist
Slovakia	NPHV (Hraničná) (mg/m³)	5 mg/m³ mist
Sweden	nivågränsvärde (NVG) (mg/m³)	10 mg/m³ mist
Sweden	kortidsvärde (KTV) (mg/m³)	5 mg/m³ mist
Portugal	OEL STEL (mg/m³)	10 mg/m³ Aerosol
Portugal	OEL - Ceilings (mg/m³)	5 mg/m³ Aerosol

Exposure-value for oil mist

: 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).

### 8.2. Exposure controls

Appropriate engineering controls Personal protective equipment

- : Large quantities: Contain large spillage with sand or earth.
- : Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.



Materials for protective clothing

Hand protection

Eye protection

Skin and body protection

Respiratory protection

Environmental exposure controls

Consumer exposure controls

Other information

: PVC gloves. Neoprene or nitrile rubber gloves.

: In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

: Eye protection should only be necessary where liquid could be splashed or sprayed.

: No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.

: Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65 °C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

: See Heading 12. See Heading 6.

: PVC gloves. Neoprene or nitrile rubber gloves.

: Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : liquid
Appearance : liquid.
Colour : Light brown.
Odour : characteristic.
Odour threshold : no data available
pH : no data available

Relative evaporation rate (butylacetate=1) : < 0.1

Melting point : no data available

10/01/2020 EN (English) 4/7

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Freezing point :  $-40 \, ^{\circ}\mathrm{C}$  Boiling point :  $>280 \, ^{\circ}\mathrm{C}$  Flash point :  $226 \, ^{\circ}\mathrm{C}$  Auto-ignition temperature :  $>240 \, ^{\circ}\mathrm{C}$ 

Decomposition temperature : no data available Flammability (solid, gas) : no data available Vapour Pressure 20 ℃ : < 0.1 hPa Relative vapour density at 20 ℃ : > 1 (air=1) Relative density : no data available Density : 0.842 kg/l Solubility : insoluble in water.

Log Pow : > 3

Log Kow : no data available
Viscosity, kinematic : > 20.5 cSt
Viscosity, dynamic : no data available
Explosive properties : no data available
Oxidising properties : no data available
Explosive limits : 0.6 - 7 vol %

9.2. Other information

VOC content : 0 %

Other properties : Gas/vapour heavier than air at 20'C.

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Stable under normal conditions of use.

#### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

#### 10.4. Conditions to avoid

Moisture. Overheating

### 10.5. Incompatible materials

Strong oxidizing agents. strong acids

## 10.6. Hazardous decomposition products

CO, CO2, POx, NOx, SOx, H2S. Metallic oxides.

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

Skin corrosion/irritation : Not classified Serious eve damage/irritation : Not classified Respiratory or skin sensitisation : Not classified Germ cell mutagenicity Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : Not classified STOT-repeated exposure : Not classified Aspiration hazard : Not classified

Other information : Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products. Likely route of

exposure: ingestion, skin and eye.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecology - general : Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

10/01/2020 EN (English) 5/7

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ecology - water

: This product floats on water and may affect the oxygen-balance in the water.

#### 12.2. Persistence and degradability

ENEOS Sustina 0W-20	
Persistence and degradability	Not readily biodegradable.

#### 12.3. Bioaccumulative potential

ENEOS Sustina 0W-20	
Log Pow	> 3
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.

#### 12.4. Mobility in soil

ENEOS Sustina 0W-20	
Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

No additional information available

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not discharge into

drains or the environment.

Additional information : Hazardous waste

Ecology - waste materials : Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden.

Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at

hazardous or special waste collection point.

European List of Waste (LoW) code : 13 02 05\* - mineral-based non-chlorinated engine, gear and lubricating oils

#### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

Not regulated for transport

### 14.2. UN proper shipping name

Not applicable

### 14.3. Transport hazard class(es)

Not applicable

### 14.4. Packing group

Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

### 14.6.1. Overland transport

No additional information available

#### 14.6.2. Transport by sea

No additional information available

### 14.6.3. Air transport

No additional information available

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

10/01/2020 EN (English) 6/7

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 0 %

#### 15.1.2. National regulations

Water hazard class (WGK) : 3 - Highly hazardous to water

#### 15.2. Chemical safety assessment

No additional information available

### **SECTION 16: Other information**

### Full text of R-, H- and EUH-statements:

Asp. Tox. 1	Aspiration hazard, Category 1
H304	May be fatal if swallowed and enters airways.
EUH210	Safety data sheet available on request.

#### SDS EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

10/01/2020 EN (English) 7/7